

# **Gold Box** LINEAR REGULATED AC-DC triple isolated outputs

Δ

- Shipped Within 3 Days
- All Models U.L. Recognized
- CE Certified
- Five Year Warranty



Ε

Ξ

## Don't forget these facts about Acopian....

- Fast Shipping? Acopian invented it! For over half a century, Acopian has built and shipped millions of power supplies within 3-DAYS after receipt of order. And we still do today! View our 3-DAY Shipping Promise: <a href="https://www.acopian.com/3dayship.html">www.acopian.com/3dayship.html</a>
- You ALWAYS talk to a real person when you call Acopian.
- Acopian power supplies last a <u>very long time</u>!
- You can email <u>3day@acopian.com</u> anytime for 24/7 product support.
- The *Online System Builder* (<u>www.acopian.com/SystemBuilder</u>) is a convenient way to get your own custom power supply or power system (and most ship within 9 Days).
- You can order Acopian power supplies factory direct.
- ALL Acopian products are made in the USA.



Easton, PA & Melbourne, FL 1-800-523-9478 • www.acopian.com Order Factory Direct Made in USA The Greatest Engineers Choose Acopian!

## GOLD BOX TRIPLE ISOLATED

## Gold Box TRIPLE ISOLATED OUTPUTS

LINEAR REGULATED AC-DC

- Shipped Within 3 Days
- All Models U.L. Recognized
- Five Year Warranty



**Triple isolated output power supplies** provide the features and characteristics of three supplies in one compact, easy-to-use package. They are available in the voltage combinations most frequently required for driving microprocessors and associated circuitry.

#### SPECIFICATIONS

**Input Voltage:** 105-125 VAC, 50-400 Hz, single phase. **Polarity:** Outputs are floating. Each output may be independently connected to provide any combination of positive and negative voltages. Outputs may be floated up to 300 volts above ground.

Temperature Coefficient: 0.02%/°C (Typical).

Ambient Operating Temperature: -10 to  $+60^{\circ}$ C. No derating required.

Storage Temperature: -55 to +85°C.

Accessory Mounting Kits: See page H3.

#### **OPTIONS**


**Overvoltage Protection:** Separate overvoltage protection circuit on each output. Add prefix "3V" to model number.

Terminal Strip Cover: Clips on. To order, add suffix "M" to model number.

**230 Volt Input:** Add suffix "–230" to the model number. Requires two additional days.

Nominal	Adjust	Output	Regulation		Ripple		
Output Voltages	Range ± V	Current Amps.	Load ±%	Line ±%	mV RMS	Model	Case Size
5 5 12	.25 .25 1	3.0 1.0 .600	.15 .15 .15	.15 .15 .15	1 1 1	5512T6A	GT6
5 5 12	.25 .25 1	6.0 2.0 1.2	.15 .15 .15	.15 .15 .15	1 1 1	5512T9A	GT9
5 9 12	.25 1 1	6.0 1.4 1.2	.15 .15 .15	.15 .15 .15	1 1 1	5912T9A	GT9
5 12 12	.25 1 1	2.0 .300 .300	.15 .15 .15	.15 .15 .15	1 1 1	51212T5A	GT5
5 12 12	.25 1 1	3.0 .600 .600	.15 .15 .15	.15 .15 .15	1 1 1	51212T6A	GT6
5 12 12	.25 1 1	6.0 1.2 1.2	.15 .15 .15	.15 .15 .15	1 1 1	51212T9A	GT9
5 12 12	.25 1 1	8.0 1.3 1.3	.15 .15 .15	.15 .15 .15	1 1 1	51212T13A	GT13
5 12 12	.5 1 1	15.0 2.0 2.0	.15 .15 .15	.15 .15 .15	1 1 1	51212T11A	HT11





8-32 Type F self-tapping screws. They should extend at least 5/16" (0.312") into the power supply case.

Case Size	L	w	н	м	v	Y	D	Е	Q	R	s	т	Approx. Weight
GT5	5.09	5.12	3.44	3.0	4.50	3.0	1.06	1.37	.56	3.75	2.75	1.75	4 lb. 14 oz.
GT6	6.59	5.12	3.44	4.0	4.50	3.0	1.06	1.37	.56	3.75	2.75	1.75	5 lb. 8 oz.
GT9	9.25	5.12	3.44	6.0	4.50	3.0	1.06	1.37	.56	3.75	2.75	1.75	7 lb. 4 oz.
GT13	13.25	5.12	3.44	10.0	4.50	3.0	1.06	1.37	.56	3.75	2.75	1.75	12 lb.
HT11	11.25	7.37	5.12	8.0	6.75	4.56	2.18	3.25	1.13	4.88	3.88	2.88	18 lb. 4 oz.
HT16	16.00	7.37	5.12	11.0	6.75	4.56	2.18	3.25	1.13	4.88	3.88	2.88	26 lb.

All dimensions in inches.	
---------------------------	--

Nominal Output	Adjust Range	Output Current	Regulation Load Line		Ripple mV		Case
Voltages	±Ϋ	Amps.	± %	± %	RMS	Model	Size
5 12 12	.5 1 1	20.0 3.0 3.0	.15 .15 .15	.15 .15 .15	1 1 1	51212T16A	HT16
5 15 15	.25 1 1	2.0 .250 .250	.15 .15 .15	.15 .15 .15	1 1 1	51515T5A	GT5
5 15 15	.25 1 1	3.0 .500 .500	.15 .15 .15	.15 .15 .15	1 1 1	51515T6A	GT6
5 15 15	.25 1 1	6.0 1.0 1.0	.15 .15 .15	.15 .15 .15	1 1 1	51515T9A	GT9
5 15 15	.25 1 1	8.0 1.1 1.1	.15 .15 .15	.15 .15 .15	1 1 1	51515T13A	GT13
5 15 15	.5 1 1	15.0 1.5 1.5	.15 .15 .15	.15 .15 .15	1 1 1	51515T11A	HT11
5 15 15	.5 1 1	20.0 2.5 2.5	.15 .15 .15	.15 .15 .15	1 1 1	51515T16A	HT16

Online Ordering and Instant Quotes for ALL Acopian power supplies at www.acopian.com 131 Loomis Street, Easton, PA 18045 • Phone: (610) 258-5441 • FAX: (610) 258-2842





# **MOUNTING KITS**

SIDE

MOUNTING

## WALL MOUNTING KITS

These kits provide a way of mounting power supplies on a wall or panel when the other side of the mounting surface is inaccessible. Each kit consists of four aluminum brackets and four machine screws for fastening them to the power supply, effectively adding mounting flanges to the power supply.

### For 'Gold Box' and (modular) 'High Voltage' power supplies:

**GB8 Mounting Kit** (#8-32 mounting holes)

Can be used on these case sizes:

CM6, CM9, CM13, CH11, CH16, DG5, DG6, DG9, G3, G5, G5D, G6, G9, G13, GT5, GT6, GT9, GT13, H8, H11, H16, HD345, HD355, HA349, HA359, HT11, HT16, LM6A\*, LM8A\*, LM10A\*, M6, M9, M13, RM6, RW6 TG5, TG6, TG9, TG13, TH11, WG7, WM6, WM9, Y3, Y5, Y6, YH11, YA \*For rear mounting brackets <u>horizontally</u> on *LM cases only*, use GBR Mounting Kit

### For 'Narrow Profile' power supplies:

**NP6 Mounting Kit** (#6-32 mounting holes) Can be used on these case sizes: AMC, CN8T, DN6B, DN6A, DN8A, DN8, F6T, F8T, N8T, WL7, WL9, WN6A, WN6B, WN8, WN8A, WN8B, TN6T

NP6L Mounting Kit (#6-32 mounting holes)

Can be used on these case sizes:

CN8H, N8H, TN8H

Model NP6L consists of two brackets 1.5" long as shown above, and two 2.5" long brackets (to extend beyond heat sink).

## DIN RAIL MOUNTING KITS

<u>CH35DIN Mounting Kit</u> (Horizontal mounting) Can be used on these case sizes: RM6, RW6

GH35DIN Mounting Kit (Horizontal mounting)

#### Can be used on these case sizes:

DG5	G3	GT5	M6	TG5	Y3
DG6	G5	GT6	M9	TG6	Y5
DG9	G5D	GT9	M13	TG9	Y6
	G6	GT13		TG13	
	G9				
	G13				
	DG6	DG6 G5 DG9 G5D G6 G9	DG6 G5 GT6 DG9 G5D GT9 G6 GT13 G9	DG6 G5 GT6 M9 DG9 G5D GT9 M13 G6 GT13 G9	610

### GR35DIN Mounting Kit (Rear mounting)

Can be used on these case sizes:

CM6	DG5	G3	GT5	HD345	M6	RM6	TG5	Y3
CM9	DG6	G5	GT6	HD355	M9	RW6	TG6	Y5
	DG9	G5D G6 G9		(GR35DIN ca ot recommen G13, GT1	ded on	case size		Y6

LR35DIN Mounting Kit (Rear mounting) LV35DIN Mounting Kit (Vertical mounting) LH35DIN Mounting Kit (Horizontal mounting) Can be used on these case sizes: LM6A, LM8A, LM10A

**NPH35DIN Mounting Kit** (Horizontal mounting)

Can be used on these case sizes:								
CN8H	DN6A	F6T	N8H	TN6T	WN6A			
CN8T	DN6B	F8T	N8T	TN8H	WN6B			
	DN8				WN8			
	DN8A				WN8A			
					WN8B			

NPR35DIN Mounting Kit (Rear mounting)

Can be used on these case sizes:

CN8H F6T N8H TN6T CN8T F8T N8T TN8H

### **NPV35DIN Mounting Kit** (Vertical mounting)


Can be used on these case sizes:								
CN8H	DN6A	F6T	N8H	TN6T	WN6A			
CN8T	DN6B	F8T	N8T	TN8H	WN6B			
	DN8				WN8			
	DN8A				WN8A			
					WN8B			

WH35DIN Mounting Kit (Horizontal mounting) Can be used on these case sizes: WM6, WM9


<u>WL35DIN Mounting Kit</u> (Vertical mounting) <u>WLH35DIN Mounting Kit</u> (Horizontal mounting) Can be used on these case sizes: WL7, WL9



LR35DIN







Acq

NOR HORNEY

REAR MOUNTING

BOTTOM



Online Ordering and Instant Quotes for ALL Acopian power supplies at www.acopian.com 131 Loomis Street, Easton, PA 18045 • Phone: (610) 258-5441 • FAX: (610) 258-2842

GR35DIN



ACOPIAN SELLS FACTORY DIRECT WORLDWIDE: We do not use representatives or distributors. Contact Acopian for technical information or a quote.

WARRANTY: Acopian power supplies are warranted to be free from defects in material and workmanship for a period of five years (encapsulated devices, for one year) from date of original shipment. Acopian's obligation under this warranty is limited to repairing any power supply returned to the factory Service Department in Easton, PA or Melbourne, FL, and replacing any defective parts. Mini Encapsulated power supplies are not repairable. Authorization must be obtained from Acopian before a power supply may be returned for repair. Units must be well packed when shipping to Acopian; the repair of any damage incurred during shipment will be charged. Transportation charges are to be paid by the purchaser. A reinspection and handling charge will be applied to returned units found to have no defects. If a failure has been caused by misuse, operation in excess of specifications, or modification by the customer, repairs will be billed at cost; in such cases, a cost estimate will be submitted before work is started.

Acopian reserves the right to make changes or improvements in its products without incurring any obligation to install the same on products previously manufactured.

This warranty is in lieu of all other warranties, obligations, and liabilities, expressed or implied, and is the purchaser's exclusive remedy. Acopian makes no warranty, either express or implied, of merchantability, fitness for a particular purpose or otherwise. In no event shall Acopian be liable whether in contract, tort, or negligence, for special, indirect, incidental or consequential damages of any kind, including loss of business or profits, or any other losses incurred by the purchaser or any third party, the Customer's remedies being limited, at Acopian's option, to replacement, repair or credit at the price on the date of claim.

The validity, performance and construction of all terms and conditions and any sale made by Acopian shall be determined by the law of Pennsylvania, without regard to its conflict of law principles, and all parties to the transaction expressly consent to the jurisdiction of such courts and consent to the venue of the Court of Common Pleas for Northampton County, Pennsylvania.

PRICES: The prices shown are F.O.B. our factory; Easton, PA or Melbourne, FL. ('EXW Factory' if outside the 50 United States.) All prices and specifications are subject to change without notice.

TERMS: Net 30 days, subject to credit approval. Visa, MasterCard and American Express also accepted.

**SHIPPING:** Location permitting, small shipments are made by United Parcel Service, FedEx, DHL (international orders) or by Parcel Post; larger shipments, by insured motor freight collect. Shipments can be made by air upon request. Risk of loss shall be F.O.B. Our Factory, even in cases where freight may be prepaid or allowed to destination by Acopian. If equipment is received in damaged condition, it is the customer's responsibility to contact the carrier and file a claim for damages.

**TIME FOR DELIVERY:** The time for delivery quoted by Acopian is the time required to ship from our plants. We will not be liable for delays in delivery caused by any reason beyond our control, including but not limited to acts of God, casualty, civil disturbance, labor disputes, transportation or supply difficulties, or any interruption of our facilities, and the quoted time for delivery shall be extended during the continuance of such conditions and for a reasonable time thereafter. In no event will Acopian be liable for any premium transportation, reprocurement, or similar costs incurred by the Customer as a result of conditions beyond Acopian's control resulting in Acopian's inability to deliver product in accordance with customer's requested delivery schedules.

**QUANTITY DISCOUNTS:** Discounts are available to quantity buyers and are dependent upon the order quantity and the manufacturing scheduling anticipated by the order, and apply only to the quantity and delivery ordered. Partial shipments are considered as separate orders for discounting purposes.

EXPORT ORDERS: A minimum export documentation charge of \$60.00 applies. (A minimum charge of \$25.00 applies on orders to certain U.S. territories requiring customs forms.)

**MOISTURE/FUNGUS PROOFING:** Power supplies can be furnished with a moisture and fungus resistant varnish applied to interior surfaces. To order, add the suffix letter F to the model number. This option requires two additional days and is not available on High Voltage, Mini Encapsulated, Rack Mounting, and Gold Box Switching models.

#### TAGGING: Add \$10.00 to price.

TEST DATA: Cost, \$35.00 or 2% of order, whichever is greater.

SPECIAL MODELS/MODIFICATIONS: Cataloged models can be altered at the factory to meet special requirements. Contact the Applications Engineering Department to discuss your needs.

PARTS: The designs used in Acopian power supplies utilize standard components to the greatest practical extent. When replacements are required, the types originally used, or their equivalents, can usually be obtained most quickly from a local electronic components distributor.

Special components, such as transformers, are stocked at the factory warehouses. Contact the Applications Engineering Department for information on the parts required, referencing the model number of the power supply, the circuit designation of the component, and a description.

PURCHASE ORDER ACCEPTANCE: Orders are accepted subject to Acopian's Terms and Conditions. Any Terms and Conditions of any Purchaser's order, agreement, or understanding which are in addition to or inconsistent with Acopian's shall not be binding upon Acopian unless made in writing and accepted over the signature of an authorized officer of Acopian. Orders shall not be considered accepted until entered into production at our plant. Acopian reserves the right to refuse any order. All typographical and clerical errors are subject to correction by Acopian.

**RETURNED GOODS:** Acopian products are built on a per-order basis, and ordinarily no credit can be extended for their return. No goods will be accepted for return unless authorized in writing by Acopian.

**CHANGES:** The customer may, by a written notice, request changes within the general scope of the order, in the drawings, designs or specifications; method of shipment; and place of delivery. If any such change causes an increase or decrease in the cost, or the time required for the processing of any part of the order, an equitable adjustment shall be made in the price or delivery schedule, or both, and the order shall be modified in writing accordingly.

CANCELLATION: Suspension or cancellation of orders may be made only upon our written approval and on terms that will indemnify us against all loss.

**OVERTIME:** It is anticipated that any order will be processed during regular working hours on regular working days. If for any reason the Purchaser requests Acopian to process the order, or any portion of it, outside of such regular working hours, any overtime or other additional expense occasioned thereby shall be billed to and paid by the Purchaser as an extra cost. Acopian reserves the right to decline to process the order outside regular working hours.

**CUSTOMER DELAY OF WORK:** If the performance of all or any part of the work is delayed or interrupted by Customer's failure to act within the time specified (or within a reasonable time if no time is specified) and such act is not expressed or implied by the order, an adjustment shall be made in the cost of performance of the order caused by such delay or interruption and the order modified in writing accordingly. Adjustment will also be made in the delivery or performance dates and any other contractual provisions affected by such delay or interruption.

**GOVERNMENT SPECIFICATIONS:** Pricing is based upon industrial-grade construction, marking, packing, and packaging. Exception is taken to any MIL specifications, and to any requirements for the use of special forms, documentation other than quoted, and Government Source Inspection. Acopian must decline to quote on any other basis.

APPLICATIONS ASSISTANCE: Questions regarding the specifications, features, and use of any Acopian product should be directed to the Applications Engineering Department. A staff of power supply specialists will be pleased to assist you.

ACOPIAN IS AN ISO 9001 CERTIFIED COMPANY

